



Innovation. Passion. Commitment.

SEC PIR



PIR MOTION SENSOR

FEATURES

- Dual Element Pyroelectric sensor
- Wall mounted
- Latest Technology Digital Signal Processor (DSP)
- Pet Immunity up to 25 kg.
- Detection Range 15m
- Detection angle 110°
- Sealed optics
- Excellent RFI and EMI Immunity
- Selectable Pulse Count
- Walk Test

TECHNICAL SPECIFICATIONS

Sensor	Dual Element Pyroelectric
Detection range	12m, 110°
RFI Immunity	Ave. 20V/m (10~1000MHz)
Power Supply	10 ~ 15V DC, 12V Typical
Current Consumption	20mA, 12V DC
Alarm Output	NC/NO 30V DC, 0.2A max.
Alarm Duration	2 seconds
Pulse Count	Single/Double
Tamper Switch	Cover Open activation
Operating Temperature	0° to 50° Celcius
Walk Test LED	Red, can disable
Detection Speed	0.3 to 1 m/s
Reverse Polarity Protection	Through Diode
Mounting Bracket	Multi-Rotational ball type
Dimensions	85mm X 52mm X 39mm (without bracket)
Colour	White
Housing	ABS
Accessories	Mounting bracket, screws and fillings.

www.securicoelectronics.com

WIRED ACCESSORIES