



Innovation. Passion. Commitment.

SEC SD2



SD 2000

FEATURES

- Micro-Controller Based
- 3 Messages
- 45 Telephone Numbers
- Extremely User Friendly
- Separate Intrusion Message
- Separate Fire Message
- Special Help Message
- Individual Intrusion & Fire Zones
- Silent Help Button
- 20 Second Recording Time For Each Message
- Operates With Both Tone & Pulse
- Message Playback
- Telephone Number Check
- Non-Volatile Memory
- 13 Key Backlit Keypad
- Power Status Led
- Dialing Status Led
- Program Status Led
- Self Test On Reset
- Line Overriding
- Sound Precision Switch
- Musical Audio Indication
- 10000 Code Combinations
- In-Built Tamper Switch
- White ABS Housing

TECHNICAL SPECIFICATIONS

ELECTRICAL

Operating voltage: 12V DC

Quiescent current: 50ma

Current with dialing & message play: 150ma

ENVIRONMENTAL

Operating Temperature: 0c to 45C

Storage Temperature: -20C to 60C

Maximum humidity: 95% non-condensing

Environment: residential / commercial / light Industrial

PHYSICAL

Dimensions: 199 mm x 110mm x 4 5mm

www.securicoelectronics.com

SPEECH DIALER