



Innovation. Passion. Commitment.

## SEC WMC 4S



4 CORE

### Technical Specifications

#### Design Details

Size	:	7/0.39 X 4 Core Sheathed Cable
Inner Conductor	:	Annealed Bare Copper Conductor
Type	:	Multi Strand
Size	:	1 \ .0.13 mm (7 wires of 0.13 mm)
Core Dia	:	0.90 mm (nominal)
Core Colour	:	Red , Yellow , Blue & Black
Insulation	:	P.V.C. Type -A As Per IS 5831
Insulation Thickness	:	0.25 mm nominal
Outer Sheath	:	ST -1 Type as per IS 5831 1984
Outer Sheath Thickness	:	0.60 mm (min)
Outer Sheath Colour	:	White

#### Electrical Properties @ 20°C

DC Resistance	:	226.6 Ohms Max Per KM
Insulation Resistance	:	36.7 M Ohm P. KM
Minimum Bending Radius	:	Cable Dia X 10
Temperature range	:	-10 DEG C to 70 DEG C

#### Mechanical Tests of P.V.C.

Tensile Strength of Insulation	:	12.5 N \ mm sq ( minimum)
Tensile Strength of Outer Sheath	:	12.5 N \ mm sq ( minimum)
Elongation of Insulation	:	150 % ( minimum)
Elongation of Outer Sheath	:	150 % ( minimum)

SEILDS24H23\_V1

www.seuricoelectronics.com

INTRUDER ALARM CABLE