



Innovation. Passion. Commitment.

SEC GLD



GAS LEAK DETECTOR

WIRED INTRUDER ALARM SENSORS

www.securicoelectronics.com

FEATURES

- LED display of the alarm LEL
- Microprocessor controller
- AC 110V-230V wide range of operating voltage
- High reliability sensor
- Indication of automatic fault checking
- Manual test / automatic reset function
- Green Led indication for power supply
- Red Led indication for Alarm
- Yellow Led indication for faulty
- Red and Yellow Led flashing alternately for warm-up
- Simple wall mounting design

Technical Specifications

Operating voltage: DC 12V or AC110V-230V 50-HZ

Stand by current: <100mA (DC12V) Low Power Consumption <50mA

Alarm current: <160mA (DC12V) Low Power Consumption <100mA

Power consumption: <3W (AC220V power supply)

Alarm LEL: 5% LEL

Operating Temperature: -10°C -50°C

Relative humidity: 10% -95%

Buzzer: >70dB 1 meter

Alarm Mode: Sound and light alarm / network alarm / solenoid valve output / wireless signal 315 MHZ or 433 MHZ optional

Transmission Distance: Open distance of 100 meters (Wireless type) optional

Warm up time: 180 sec

Dimension: 73 X125X38mm