



Innovation. Passion. Commitment.

# SEC - CIDP1 IR10



## FEATURES

- 1/4" Progressive Scan CMOS
- Up to 1 megapixel high resolution
- 10 m IR range
- Dual stream
- Digital Wide Dynamic Range
- 3D DNR (Digital Noise Reduction)
- Mobile Monitoring via Securico App
- Login security protection and password strength detection

## TECHNICAL SPECIFICATIONS

CAMERA	
Image Sensor	1/4" Progressive Scan CMOS
Min. Illumination	0.01Lux @(F1.2,AGC ON), 0 Lux with IR; 0.028 Lux @(F2.0,AGC ON), 0 Lux with IR
Shutter Speed	1/3 s to 1/10,000 s
Lens	4mm, horizontal view angle: 73.1° (2.8mm,6mm,8mm,12mm optional)
Lens Mount	M12
Day & Night	IR cut filter with auto switch
3-Axis Adjustment	Pan: 0° to 360°; Tilt: 0° to 75°; Rotation: 0° to 360°
DNR	3D DNR (Digital Noise Reduction)
Wide Dynamic Range	Digital WDR
COMPRESSION STANDARD	
Max. Resolution	1280×720
Main Stream	50Hz: 1280×720@25fps 60Hz: 1280×720@30fps
Sub-stream	50Hz: 704×576@25fps 60Hz: 704×576@30fps
Others	Mirror, BLC (areas configurable), Brightness, Contrast, Saturation
NETWORK	
Alarms	Motion Detection, Dynamic Analysis, Video Tampering, Network Disconnected, IP Address Conflicted
Protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour
Standard	ONVIF, ISAPI
General Function	Anti-Flicker, Dual Stream, Heartbeat, Mirror, Password Protection, Privacy Mask, Watermark
INTERFACE	
Communication Interface	1 RJ45 10M/100M Ethernet port
GENERAL	
Operating Conditions	-10 °C to 40 °C (-14 °F to 104 °F), Humidity 95% or less (non-condensing)
Power Supply	DC12V ± 10%
Power Consumption	Max. 3.2W Max. 9W with pan and tilt
IR Range	10 meters
Dimensions	Φ110mm×80.9mm (Φ4.3"×3.2")
Weight	190g (0.4 lb)